

Documentation

Requirements

- ▣ JQuery 1.4.2 or greater (earlier version may work but they are untested.)
- ▣ Umbraco 4.5.x or greater (New XSLT syntax used)

Configuration Steps

1. install package,
2. add jquery plugin call to template: `<script type="text/javascript" src="/scripts/rocketfuel/rfslider.js"></script>`
3. ensure that your page/node is allowed to have RF-Slides as children.
4. Add the rfSlider Macro in the HTML editor or on the desired page template.
5. Add RF-Slides to populate the slider.

In this Package:

- ▣ Data Types - Anchor Targets (allows slide links to open new windows)
- ▣ Macro - rfSlider.xslt
- ▣ Scripts - rfslider.js and jquery 1.4.2 //be sure that your page references your js files.
- ▣ Images - Slider navigation images

Notes

- ▣ Tested to only have one rfSlider per page.
- ▣ Multiple Sliders do not work independently. JQuery plugin will require revisions.

Default Settings

The rfSlider defaults are called in when the slider is initiated:

```
var settings = {  
'sliderwidth' : 400, //width of single slide  
'sliderheight' : 200, //height of single slide  
'holder' : '.rfslidemask', //css class used to mask the slides  
'slidetime':600, //css class used to mask the slider  
'slideinterval':3000, //time allotted between slides  
'slidetransition':'wipe' // fade or wipe transitions are supported  
};
```

Overriding Default Settings

In the XSLT you can change the override of your Slider with the following call:

```
$( "#placeholder" ).rfSlider("init",{ 'sliderwidth' : 400, 'sliderheight' : 200 }); //add the setting that you need to adjust in order to override it.
```

Last edited by ChrisDunsing on 4/14/2011 7:10:17 PM, Version: 6